

# GO Carbon Fibre Spring Plate

## Internal Shoe Stiffener by Corthotics

A simple and effective solution for limiting motion across the forefoot and aiding propulsion



### **FEATURES:**

- Extremely thin, light and durable made from premium quality pre-preg carbon
- Pre-shaped left or right and available in 4 sizes
- Contoured design to provide ideal toe spring and heel elevation for most athletic, walking and orthopaedic footwear designs
- Excellent interface with custom foot orthotics
- A practical alternative to some common shoe modifications

### **CLINICAL INDICATIONS:**

- Post-surgical care option when transitioning from post-op shoe to regular footwear after bunion, hammertoe and other forefoot surgeries.
- Management solution for turf toe, forefoot stress fractures, sesamoiditis and Lisfranc injuries.
- Protection and toe off assistance for pathologies affecting the midfoot and forefoot including rheumatoid arthritis, structural hallux limitus or rigidus, Freiberg's disease, diabetes and forefoot amputations.



Tel: +64 9 482 4370

Email: info@ganleyorthotics.co.nz Web: www.ganleyorthotics.co.nz



### **CARBON FIBRE SPRING PLATE**

### **CONSIDERATIONS:**

- Maximum body weight tolerance is 125kgs.
- Important to use in shoes with adequate forefoot rocker profile.
- Plates are not returnable for credit however size exchange requests can be made for UNUSED AND UNMODIFIED PLATES ONLY.

### PRODUCT GUARANTEE

The Paris Carbon Fibre Spring Plate is guaranteed against breakage for 6 months.

- Minor grinding (forefoot shape and/or length) will not affect durability or nullify warranty.
- Heating and reshaping will cause delaminating and will nullify warranty.

SHIP TO (ALL FIELDS REQUIRED)					
ATT:					
CLINIC:					
ADDRESS:					
CITY:					
POSTCODE:					
PHONE:					
EMAIL:					

### **SUBMIT THIS FORM BY:**

- ① FAX 09 482 4097
- ② EMAIL info@ganleyorthotics.co.nz

### ORDER DETAILS - SIZING & UNITS

SIZE	DEVICE LENGTH tolerance +/- 2мм	4	LEFT / RIGHT	QTY
XS	239мм	Z	L	
S	259мм	INSOLE	L	
М			L	
L	298мм	_ NS∪	L	
XS	239мм	MEASUREMENT	R	
S	259мм	m Z H	R	
М	279мм		R	
L	298мм		R	